

CeNano Sealant for Automobile Panes

Instructions for use

Product description

CeNano sealant for automobile panes performs a water and oil repellent glass surface. It facilitates an excellent roll-off behaviour for rainwater, greatly simplifying the removal of dirt, insects and ice/frost. The coating reduces the need to use the windscreen wiper unit and significantly improves visibility.

For best results, proceed as described below:

1. Cleaning the panes

Ensure that the pane is completely dry and clean. Use nanotol primer for optimum cleaning to remove even particles invisible to the naked eye

2. Check the cleanness of the pane

by spraying some water on the surface. The water should form a uniform film and not collect into droplets. If droplets are formed, this is a clear indication of the presence of dirt and grease.

3. Sealing with CeNano sealant for automobile panes

During application we recommend wearing protective gloves – CeNano sealant for automobile panes dehumidifies.

- Coat the panes in sections with a soft, dye- and lint-free cloth (i.e. dish cloth or linen.)
- Apply and polish the sealant in circular movements and spread evenly. Multiple applications improve the result for a reliable coating.
- After coating, the entire pane should be covered by a grey film – this is an indication that the surface is completely coated!!

- Wipe away the grey film with a cotton rag or a cellulose cloth until the pane is completely clear
- If necessary, use some spirit for wiping. Glass detergents should be used not earlier than an hour after coating. Do not use any micro fibre cloths on the coated pane!

Result: Water on the coated pane collects into droplets and rolls-off.

For best results:

- At high moisture levels, coating durability can be improved by wiping the pane with a small quantity of alcohol or spirit prior to coating.
- Coat smaller sections at a time if working at ambient temperatures > 30 °C, otherwise the sealant will dry too quickly.
- Avoid direct solar radiation during the coating process.

Cleaning the panes after the coating

Do not use the wiper earlier than an hour after coating. Clean the panel with a wet sponge or a wiper if anti-stick effect weakens over the time. Micro fibre cloths can affect coating results. Note that especially fresh coating which has not yet set can be damaged by micro-fibre cloths. It will be still necessary to use the wiper unit to remove superficial dirt. We strongly recommend to use intact wipers to avoid dazzle effect by residual water.

Read carefully

The application instructions on this sheet are based on extensive research but do not in any manner diminish the responsibility of the user to ensure that the product and application method described herein are suitable. Note that the manufacturer will accept no liability unless purpose and application type have been agreed upon in writing. Observe the procedures indicated in the instructions for use